



## PC+AL Tube Light

**T8** 600mm / 1200mm / 1500mm

**C-LIGHT**  
**PROJECT** BVBA





## PC+AL Tube Light

**T8** 600mm / 1200mm / 1500mm

### Introduction

- AL+PC LED Tube light adopts LM-80 2835 SMD LED with high brightness and slight light decay.
- Excellent cooling system with >0.8mm thickness AL6063 aluminum heatsink.
- Clear or frosted cover optional. V0 fire-rated PC cover, up to 95% light transmittance.
- Reliable isolated driver solutions with 3750V voltage withstand, branded high quality capacitor and IC solution ensures excellent working performance.
- Application: Suitable for commercial and residential applications like office, supermarket, shop, school, hotel, restaurant, workshop, warehouse, home etc.



### Appearance Parameters

Model	Dimension (mm)				Product Size (mm)	Net Weight (kg)
	A	B	C	D		
UP-T810W600	605	588	28.5	32.2	605x28.5x32.2	0.18
UP-T818W1200 UP-T820W1200	1214	1198	28.5	32.2	1214x28.5x32.2	0.31
UP-T825W1500	1514	1498	28.5	32.2	1514x28.5x32.2	0.4

### Technical Specifications

Voltage: AC100-277V	Lifespan: 40000hrs
Power: 10W / 18W / 20W / 25W	CRI: ≥80
Power Factor: ≥0.9	IP: 20
Beam angle: 120°	Dimmable: No
CCT: 3000K 4000K 5000K 5700K	Diffuser: Clear / Opal

Model	Non-DIM Lumen (±5%)			
	3000K	4000K	5000K	5700K
UP-T810W600	1000	1020	1035	1050
UP-T818W1200	1800	1840	1870	1880
UP-T820W1200	2040	2050	2080	2100
UP-T825W1500	2510	2575	2600	2620